
artigo

ENGLISH

Artigo flooring products are delivered on wooden pallets. They are packed in cardboard boxes for tiles or wrapped by foamed film, and sometimes paper, for rolls. The entire pallet is placed under stretch film, sometime within protection wooden cages (other packaging may apply).

The packaging and the protection method for the delivery may vary according to quantity, destination, means of transportation, product, client specification. Artigo retains the right to modify the packaging without notice.

HANDLING

Handling and storage of pallets can be hazardous for the working staff due to the risk linked to a package fall, it is therefore recommended that it is done only by trained and authorized personnel, capable to use appropriate and maintained equipment (forklift, pallet jack).

Precautions regarding handling

Avoid any shock/bump/hit that may mark, shred, or damage anyhow the flooring material, also through the packaging.

STORAGE

Storage ideal conditions for temperature and humidity are : 15°C ÷ 30°C, HR 40% ÷ 70%.

Storage conditions may be temporarily different: -10°C ÷ 35°C, HR 30% ÷ 80%; it is mandatory to acclimatise and condition the flooring at least 72 hours before use at the ideal storage conditions (longer time might be necessary if the material spent some time at very different temperatures).

The material shall be stored in the room/area where it will be installed at least 48 hours before the laying, at a temperature $\geq 15^{\circ}\text{C}$ ($\leq 30^{\circ}\text{C}$) for the subfloor and $\geq 18^{\circ}\text{C}$ ($\leq 30^{\circ}\text{C}$) for the air; the humidity shall be between 40% and 60%. The sheets shall be unrolled and left to rest flat before cutting and laying.

Such temperature/humidity conditions must be kept during the complete installation and also at least 72 hours afterwards (for more details please refer to our official Laying Instructions).

Maximum storage period: 5 years.

During the storage always keep the identification labels on the rolls until use; they contain important information required in case of dispute/claim.

Precautions regarding storage

In order to avoid damages to the floor covering, it is mandatory to respect the following instructions:

- always store the material in closed and dry premises,
- always store rolls in upright position,
- avoid to stack the pallets,
- avoid to place/stack any other material on top of the rolls,

Precautions regarding storage continues

- avoid to store rolls in horizontal position,
- unfasten and release the boxes with tiles and the rolls from any tight packaging material (stretch film) to avoid compression: cut the wrapping film, remove chocks, strapping, etc,

With stretch film



Stretch film removed



- once the stretch film is removed, keep the rolls fastened by tape as they are from Artigo; if the rolls are not fastened by Artigo for any reason, please fasten them to prevent accidental falls (rubber flooring in rolls are extremely heavy),
- in case rolls are shipped in horizontal position please make sure to open the pallet and place/store the rolls in vertical position as soon as possible.
- avoid to expose the floorcovering without protection to the light (artificial and/or natural also through windows/glass),
- avoid to expose the material to water,
- avoid any exposure to bad weather of any kind,
- avoid storage of pallets directly on racks (without under pallets) due to possible break of the pallet,
- protect and prevent the rolls from falling and from the “domino effect”.

Fire protection

Suitable extinguishing agents: water, dry ice, powder.

Remarks:

In case of questions and/or doubts please contact our Technical Service at info@artigo.com

Artigo Spa

Headquarters

Loc. Carpeneto

I7014 Cairo Montenotte (SV) ITALY

Tel: +39 019509011

Fax: +39 019505513

Sales office

Via Cascina Vione 3

20079 Basiglio (Mi) Italy

Tel: +39 0290786415

Fax: +39 0290786449

www.artigo.com